


FOOD DELIVERY / PICK UP
CATERING
MEDICAL
EVENTS




Made
in France



FUNCTIONAL

250 kilos load and
1.3 m³ useful storage



PERFORMING

Between 60 and 70
kilometers of range



UNIQUE

Temperature maintained
between +4 and -25° C



COMPLIANT

ATP FRA (positive) and FRC
(negative) certified



INTELLIGENT

Temperature recording and
monitoring
Programming of the cooling unit

DIMENSIONS

- Useful dimensions (mm) L x l x h :
3 500 x 1 100 x 1 980
- Inside dimensions (mm) L x l x h :
1 325 x 902 x 1 080
- Up to 12 boxes of 600 x 400 x 300
mm
- Capacity of a Europalette

STANDARD EQUIPEMENTS

- Door switch for :
- Count the number of door openings
- Shut down the evaporator fans
- Prevent restart in case of open door
- Secure door opening
- Stainless steel handle
- Automatic LED interior lighting
- Bumper

OPTIONS

- ATP certificate
- Interior horizontal aluminium divider
- Customizable covering

MODELS

NEGATIVE COLD LMB CELL

- Negative cold down to -25°C during 4 à 6h
(depending on topography) with 35 door
openings of less than one minute, at a tem-
perature under shelter of 30°C
- ATP certification for 6 years, renewable for
6 years
- Rear or side opening



POSITIVE COLD LBM CELL R 1234YF

- Positive cold 0°C to +4°C for 12 hours with
60 door openings of less than one minute,
at a temperature under shelter of 30°C
- ATP certification for 6 years, renewable for
6 years
- Rear or side opening



ISOTHERMAL LBM CELL

- K coefficient 0,31
- Rear or side opening



Discover our entire range



DRY
CELL



FOOD



DECK
CELL



WASTE
CELL



IKLEUSTER
THE ENERGY OF A MOVING WORLD